

channel embedded audio via the front control panel. An optional 19-inch rackmount kit is available to install the HDSC1 unit into a standard A/V rack.

HDSC1: Specifications

Package Contents:

- HDSC1 unit
- AC adapter
- User manual

Technical Specifications:

Video Formats

HD-SDI

- 1920 x 1080 50i / 59.94i / 60i
- 1280 x 720 59.94p / 60p

SD-SDI

- 720 x 525 (NTSC)
- 720 x 625 (PAL)

Digital Video Input

- 1 x BNC (HD/SD-SDI SMPTE 292M compliant)

Digital Video Output (pass-through)

- 1 x BNC (HD/SD-SDI SMPTE 292M compliant)

Analog Video Output

- 5 x component/RGB (BNC Y/G, Pb/B, Pr/R, H-Sync, Y-Sync*)
- 1 x S-Video (4-pin miniDIN)
- 1 x composite (BNC)
- 1 x composite (RCA)

*Sync on green supported

Analog Audio Output

- 2 x unbalanced stereo (RCA)
- Output channel selectable (Ch1/2, Ch3/4, Ch5/6, Ch7/8, Mix)

Sync Generator Output Signal

- Black Burst Sync: 525(NTSC), 625 (PAL)
- Tri-Level Sync: 1080 - 50i/59.94i/60i, 720 - 59.94p/60p

USB Connector

- 1 x USB (for firmware updates via a PC)

Power

- 10.8W (max)

Dimensions

- Width – 215mm
 - Height – 44mm
 - Depth - 241mm
-

Service and Support:

- 3-year limited warranty
- Access to the Canopus Registered Users Web site at www.canopus.com when you register your product in an active [Canopus User Account](#)